SCS Global Services does hereby certify that an independent assessment has been conducted on behalf of:

## AHF, LLC dba AHF Products

3840 Hempland Road, P.O. Box 566, Mountville, PA, United States

For the following product(s):

See Addendum

The product(s) meet(s) all of the necessary qualifications to be certified for the following claim(s):

## FloorScore<sup>®</sup>

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring. Also, conforms to the SCAQMD Rule 1168 - Adhesive and Sealants (October 2017).

Highest Specified Product Application Amount: 330 g/m2

Measured Concentration of Total Volatile Organic Compounds (TVOC): Between 0.5 - 5.0 mg/m3 (in compliance with CDPH/EHLB Standard Method v1.2-2017) Methylene Chloride and Perchloroethylene are not intentionally added to certified products.

Registration # SCS-FS-08496

Valid from: September 1, 2023 to May 31, 2024

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, http://www.scsglobalservices.com/certified-green-products-guide.







Stanley Mathuram, PE, Executive Vice President SCS Global Services 2000 Powell Street, Ste. 600, Emeryville, CA 94608 USA

## **Certification Addendum**

## AHF, LLC dba AHF Products

Certification: Registration # SCS-FS-08496 | Valid from: September 1, 2023 to May 31, 2024

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification;

certified products are only listed on the SCS Green Products Guide, http://www.scsglobalservices.com/certified-green-products-guide.

Addendum FloorScore®

Conformance: Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring. Also, conforms to the SCAQMD Rule 1168 - Adhesive and Sealants

(October 2017).

Highest Specified Product Application Amount: 330 g/m2

Measured Concentration of Total Volatile Organic Compounds (TVOC): Between 0.5 – 5.0 mg/m3 (in compliance with CDPH/EHLB Standard Method v1.2-2017) Methylene Chloride and Perchloroethylene are not intentionally added to certified products.

**Products:** Flooring Adhesives:

Armstrong S-202 SDT Adhesive for Static Dissipative Tile, Armstrong S-235 Premium Sheet Flooring Adhesive, Armstrong S-254 Residential Sheet Flooring Adhesive, Armstrong S-289 Releasable & Permanent Flooring Adhesive, Armstrong S-319 Roll Strong, Armstrong S-515 Clear Thin Spread Floor Tile Adhesive, Armstrong S-543 – Commercial Sheet Flooring and LVT Adhesive, Armstrong S-700 Thin-Spread Floor Tile Adhesive, Armstrong S-750 Premium Floor Tile Adhesive, S-392 - SDT Polish, S-480 Polish (Note: These products are coatings)

