PROCONNECT" PLUS



1. IDENTIFICATION

90%. Moisture Vapor Barrier Elastomeric Wood Flooring Adhesive Recommended use of the chemical and restriction on use: interior installation of flooring material over approved subfloors – glue-down installation of all engineered, solid, bamboo, cork and parquet flooring. subfloor – Solid, engineered, bamboo, cork and parquet wood flooring. Company: Bruce® Flooring 3840 Hempland Road, Mountville, PA 17554, (706) 712-5820 Emergency Telephone Number: (800) 535-5053 Other Means of Identification Chemical Family: Modified Silane blend

2. HAZARDS IDENTIFICATION

According to regulation 2012 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200 Classification of the Product: No need for classification according to GHS criteria for this product. Label Elements: This product does not require a hazard warning label in accordance with GHS criteria. Hazards Not Otherwise Classified: None known if used according to instructions. Irritation may occur when in contact with eyes and skin.

3. COMPOSITION/INFORMATION ON INGREDIENTS

According to Regulation 1994 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200 This product does not contain any components classified as hazardous under the referenced regulation.

CAS #	Content	Chemical Name
Trade Secret	15 - 30	Silyl Terminated Polyether
Trade Secret	15 - 30	Plasticizer
1317-65-3	45 - 60	Calcium carbonate
Trade Secret	1 - 5	Additives

4. FIRST AID MEASURES

General Advice: Upon contact, remove material from skin, eyes and clothing. If irritation persists, seek medical attention. If Inhaled: Remove individual to fresh air if needed. If on Skin: Wash with mild soap and water. If in Eyes: Open eyelids and flush with running water for at least 15 minutes. If Swallowed: Do not induce vomiting. Seek medical help immediately. Most Important Symptoms and Effects, Both Acute and Delayed: None expected due to nonclassification of the product. Indication of Any Immediate Medical Attention and Special Treatment Needed: Note to physician - Symptomatic Treatment

5. FIRE-FIGHTING MEASURES

Extinguishing Media Use water spray, foam, dry powder when needed. Special Hazards Arising from the Substance or Mixture Material is a mixture of organic compounds. Compounds of carbon may arise during burning. Advice for fire-fighters: Wear self-contained breathing apparatus and turn out gear. Further Information Dispose debris and contaminated clothing in accordance with regulations.

6. ACCIDENTAL RELEASE MEASURES

Further Accidental Release Measures: Slip hazard when spilled. Personal Precautions Protective Equipment and Emergency Procedures: Use personal protective clothing. Avoid contact with skin and eyes. Environmental Precautions: Do not release spilled material into natural waters.

Methods and Material for Containment and Cleaning Up:

Remove material using absorbents. Scrape off excess and place in closed DOT approved containers for disposal.

7. HANDLING AND STORAGE

Precautions for Safe Handling Do not puncture. Keep out of the reach of children. Conditions for Safe Storage, Including any Incompatibilities Keep from freezing. Avoid extreme temperatures.



PROCONNECT[®] PLUS



8. EXPOSURE CONTROL/PERSONAL PROTECTION

Advice on System Design Maintain proper ventilation. <u>Personal Protective Equipment:</u> Respiratory Protection: NIOSH respirator if needed. Use local exhaust ventilation. Do not use closed air-circulating system. Skin Protection: Chemical resistant gloves, apron, coveralls, and boots to prevent unnecessary contact. Eye Protection: Safety glasses, goggles, or face shield General Safety and Hygiene Safety Measures: Wash hands and/or face after use. Launder contaminated clothing before re-use. Always use protective equipment to avoid direct contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Medium Viscosity Liquid Odor: Mild Odor Threshold: No data Color: Off white pH Value: Not applicable **Melting Point: Not applicable Boiling Point:** No data Flash Point: Not appplicable Flammability: Non-flammable Lower Explosion Limit: Not applicable **Upper Explosion Limit:** Not applicable Vapor Pressure: Low Density: 9.4 – 10.1 lbs. per gallon Relative Density: 1.13 - 1.21 grams/cm3 Vapor Density: Low Partition Coefficient n-octanol/water (log Pow): No data Self-Ignition Temperature: Not Applicable Solubility in Water: Insoluble Miscibility in Water: Not miscible Evaporation Rate: Same as water Other Information: Moisture cure product. Product will start curing in the presence of moisture. VOC Content: 0.1 g/L (SCAQMD Rule #1168)

10. STABILITY AND REACTIVITY

Reactivity: Stable Chemical Stability: Stable Possibility of Hazardous Reactions: None, product is stable Conditions to avoid: Extreme temperatures Incompatible Materials: Water. Product is a moisture curing material. Hazardous Decomposition Products: None known

11. TOXICOLOGICAL INFORMATION

No Data Available Primary routes of exposure: Respiratory, eyes, skin. Ingestion is not likely but might cause gastric disturbances. Acute Toxicity/Effects Acute toxicity: May cause irritation upon contact. Chronic Toxicity Effects Repeated Dose Toxicity: No data available Genetic Toxicity: No data available Carcinogenicity: Not carcinogenic Reproductive Toxicity: No data available Teratogenicity: No data available Experiences in Humans: No data available

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Abide by all state, federal and local regulations

14. TRANSPORTATION INFORMATION

Proper Shipping Name: Not applicable Proper Hazard Class: Not hazardous Hazard Code: None hazardous Bill of Lading Description: Adhesives, NOI Land Transport USDOT: Not considered as a dangerous goods under transport regulations. Sea Transport IMDG: Not considered as a dangerous goods under transport regulations. Air Transport IATA: Not considered as a dangerous goods under transport regulations.

15. REGULATORY INFORMATION

 Federal Regulations:

 Registration Status:

 TSCA: Chemical in the product are either listed or exempt in the U.S. EPA TSCA inventory list.

 SARA Title III, Section 312 Hazard Class: None

 EPA SARA Title III Section 312: None

 NFPA Hazard Codes:

 Health: 1

 Fire: 0

 Reactivity: 0

 Special:

 HMIS rating:

 Health: 1

 Flammability: 0

 Physical Hazard: 0

16. OTHER INFORMATION

SDS prepared for: Bruce Flooring SDS prepared on: May 20, 2020

Bruce Flooring believes the data set forth herein is accurate as of the date hereof. Bruce Flooring makes no warranty with respect hereto and expressly disclaims all liability of reliance thereon. All data is offered solely for consideration, investigation, and verification.

