






Armstrong Flooring Commercial Adhesive Summary




	RH Limit	pH Limit	Applicator	Unit Sizes	Spread Rate	Open Time	Working Time	Traffic Time			Shelf Life	LVT	VCT	Vinyl Sheet	SDT	Wall Base	Stair Treads	Landing Tiles
								Low	Med	High								
Flip	95%	11	Spray adhesive	22 oz. Can	140-150 sq. ft. / Can	30 Min.	4 Hours	0	0	0	1 Year							
S-202	75%	9	Fine U notch (S-891) 1/32" x 1/16" x 5/64"	Gal. 4 Gal.	150 sq. ft. / gal.	60 Min.	6 Hours				1 Year			✓				
S-319	99%	12	Roll-on	Gal. 4 Gal.	300-400 sq. ft. / gal.	15 Min.	4 Hours	0	0	0	1 Year	✓						
S-515	95%	11	Fine U notch (S-891) 1/32" x 1/16" x 5/64"	Gal. 4 Gal.	285-335 sq. ft. / gal.	30 Min.	24 Hours				1 Year		✓					
S-525	90%	11	Fine U notch (S-891) 1/32" x 1/16" x 5/64"	Gal. 4 Gal.	275-325 sq. ft. / gal.	20 Min.	24 Hours				2 Years		✓					
S-1000	NTR	NTR	U-Notch 1/32"x 1/16"x 1/32"	2 gal. Pail	220-260 sq. ft. / gal.	10-20 Min.	45 Minutes	3h	4h	8h	1 Year	✓						
S-995	95%	10	U-Notch 1/32"x 1/16"x 1/32"	Gal. 4 Gal.	220-260 sq. ft. / gal.	See TDS	2 Hours	24h		48h	2 Years	✓		✓				
S-725	NA	NA	U-notch 1/16" x 1/16" x 3/32"	30 oz. Gal. 4 Gal.	300-350 lin. ft. / gal. (4" base)	0 Min.	15 Minutes				1 Year							
S-726	85%	9	Square Notch 1/16" x 1/16" x 1/16"	Gal.	125-150 sq. ft. / gal.	5-10 Min.	45 Minutes	48h		72h	1 Year					✓	✓	
S-727	NA	NA	S-728 Static Mixing Nozzle	13.5 oz. Cartridge	3/8" Bead x 25 lin. ft.	0-10 Min.	45 Minutes	24h		48h	1 Year							
S-761	NA	NA	Applicator Bottle	8 oz. Bottle	1/8" Bead x 144 lin. ft.	0 Min.	15 Minutes	2h			1 Year							
S-762	NA	NA	Applicator Pen	10 ml. Pen	250 lin. ft. per Pen	-	-				1 Year							
S-580	NA	NA	Brush or Roller	Half Gallon	200-250 sq. ft. / half-gal.	20-30 Min.	Unlimited				1 Year			✓				



-  Primary recommendation
 -  Compatible
 -  Not Compatible
 -  Not Compatible
 -  For use with certain products and/or applications. Refer to FloorExpert.com for details
- Please Note:** The primary recommendation is what is listed on product data sheets.



Armstrong Flooring Residential Adhesive Summary

	RH Limit	pH Limit	Applicator	Unit Sizes	Spread Rate	Open Time	Working Time	Traffic Time			Shelf Life	Rigid Core	Eng. Tile	LVT	Sheet
								Low	Med	High					
S-319	99%	12	Roll-on	Gal. 4 Gal.	300-400 sq. ft. / gal.	15 Min.	4 Hours	0	0	0	1 Year			✓	
S-1000	NTR	NTR	U-Notch 1/32"x 1/16"x 1/32"	2 gal. Pail	220-260 sq. ft. / gal.	10-20 Min.	45 Minutes	3h	4h	8h	1 Year				
S-295	95%	10	U-Notch 1/32"x 1/16"x 1/32"	Gal. 4 Gal.	220-260 sq. ft. / gal.	See TDS	2 Hours	24h		48h	2 Years	✓	✓	✓	✓
S-299	99% LVT 95% Sheet	12	U-Notch 1/32"x 1/16"x 1/32"	Gal. 4 Gal.	220-260 sq. ft. / gal.	See TDS	4 Hours	24h		48h	2 Years				
S-761	NA	NA	Applicator Bottle	8 oz. Bottle	1/8" Bead x 144 lin. ft.	0 Min.	15 Minutes	2h			1 Year				
S-500	NA	NA	Applicator Bottle	20 ml. Kit	50-60 lin. ft. / Kit	0 Min.	3 Hours	3h			1 Year				
S-580	NA	NA	Brush or Roller	Half Gallon	200-250 sq. ft. / half-gal.	20-30 Min.	Unlimited				1 Year				

-  Primary recommendation
-  Compatible
-  Not Compatible

-  Not Compatible
-  For use with certain products and/or applications. Refer to FloorExpert.com for details

Please Note: The primary recommendation is what is listed on product data sheets.