MATERIAL INFORMATION SHEET

I. PRODUCT IDENTIFICATION

Name: Armstrong Commercial Sheet Flooring Products Description: Homogeneous Sheet Vinyl Flooring

II. DEPARTMENT OF TRANSPORTATION INFORMATION

Shipping name: Not Classified. Hazard Class: N/A. ID #: N/A EMERGENCY ONLY CONTACT: CHEM-TEL -1-800-255-3924

III. HMIS (0=Minimal hazard; 4=severe hazard)

Health = 1 Flammability = 0 Reactivity = 0

IV. PRODUCT CONTENT

This product contains chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372. All components are on TSCA inventory. This product does not contain asbestos.

V. HAZARDOUS INGREDIENTS

(Chemical Identity; Common Name)	C.A.S. No.	<u>%</u>	OSHA PEL	ACGIH TLV
None	N/A	N/A	N/A	N/A

DESCRIPTION AND INGREDIENT INFORMATION

These vinyl flooring products are produced for commercial (architectural) marketplace use. They come in a wide variety of aesthetic designs, styles, colors, surface finishes, and sizes.

MISCELLANEOUS INFORMATION

Each of these products is classified as an "article" according to Title 29 of the Code of Federal Regulations, OSHA Part 1910.1200(c). They are formed to a specific shape or design during manufacture, have end use functions dependent upon their shape or design, and do not release any hazardous chemical under normal conditions of use.

VI. PHYSICAL DATA

APPEARANCE: Material dependent. BOILING POINT (degrees F): N/A. VAPOR PRESSURE (mm Hg @ 20 degrees C): N/A. VAPOR DENSITY (Air = 1): N/A. PERCENT VOLATILE BY WEIGHT (30 min. @ 275 degrees F): N/A. EVAPORATION RATE (Butyl Acetate = 1): N/A. SOLUBILITY IN WATER: N/A. SPECIFIC GRAVITY (H20 = 1): N/A. pH: N/A.

VII. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A. FLAMMABLE RANGE: LEL = N/A; UEL = N/A. EXTINGUISHING MEDIA: Water. SPECIAL FIRE FIGHTING PROCEDURES: Protect fire fighters from toxic products of combustion by wearing self-contained breathing apparatus. UNUSUAL FIRE AND EXPLOSION HAZARDS: None.

VIII. HEALTH HAZARD DATA

PRIMARY ROUTE(S) OF ENTRY: N/A. TARGET ORGANS: N/A. EFFECTS OF OVEREXPOSURE: N/A SKIN AND EYES: N/A. INHALATION: N/A. CARCINOGENICITY: NTP: No; IARC Monographs: No; OSHA Regulated: No. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/K. FIRST AID PROCEDURES: N/A SKIN AND EYES: N/A. INHALATION: N/A. INGESTION: N/A

IX. REACTIVITY DATA

STABILITY: N/A. INCOMPATIBILITY: N/A. HAZARDOUS DECOMPOSITION PRODUCTS: N/A. HAZARDOUS POLYMERIZATION: N/A..

X. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: N/A. WASTE DISPOSAL METHOD: Dispose of in accordance with Federal, State, and Local Waste Disposal Regulations.

Mountville, PA 17554 www.floorexpert.com Technical Services: 1-866-243-2726

ArmstrongFlooring

Commercial Sheet

Prepared 07/23

AHF Products

3840 Hempland Road

P. O. Box 566

1-000-243-2720

XI. SAFE HANDLING AND USE INFORMATION

VENTILATION: N/A. RESPIRATORY PROTECTION: N/A. SKIN AND EYE PROTECTION: N/A.

XII. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep from freezing. OTHER PRECAUTIONS: None.

XIII. WARNING

FOR PREVIOUSLY INSTALLED FLOOR COVERING
DO NOT SAND, DRY SCRAPE, BEADBLAST, OR
MECHANICALLY PULVERIZE EXISTING RESILIENT
FLOORING, BACKING OR LINING FELT. THESE
PRODUCTS MAY CONTAIN EITHER ASBESTOS FIBERS
OR CRYSTALLINE SILICA. POSSIBLE CANCER AND
RESPIRATORY TRACT HAZARD BY INHALATION. AVOID
CREATING DUST. SMOKING BY INDIVIDUALS WHO HAVE
BEEN EXPOSED TO ASBESTOS FIBERS GREATLY
INCREASES THE RISK OF SERIOUS BODILY HARM.
RFCI'S (Resilient Floor Covering Institute)
RECOMMENDED WORK PRACTICES FOR REMOVAL OF
RESILIENT FLOOR COVERINGS ARE A DEFINED SET OF
INSTRUCTIONS ADDRESSED TO THE TASK OF

XIV. NOTICE

STRUCTURES.

Various government agencies have regulations governing the removal of inplace asbestos-containing materials. If you contemplate the removal of a resilient floor covering structure that contains (or is assumed to contain) asbestos, you should determine whether such regulations apply.

REMOVING ALL RESILIENT FLOOR COVERING

The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

N/K- none known or not known.

N/A- not applicable or not available.