Lifeproof™ Resilient and Ceramic Floor Cleaner - Refill 12-March-2021 Armstrong Flooring, Inc. 2500 Columbia Ave. Lancaster, PA USA 17603 Telephone: (800) 233-3823 Page **1** of **6** 

#### SAFETY DATA SHEET

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION		
Product Identifier       :         Product Code       :         Trade Name/Synonyms       :         Recommended Use       :         Uses Advised Against       :         Supplier's name and address       :	Lifeproof <sup>™</sup> Resilient & Ceramic Floor Cleaner - Refill 316527141 337106, S-337 Ready-to-use cleaner used to refill Lifeproof <sup>™</sup> Resilient & Ceramic spray bottle for cleaning no-wax vinyl, ceramic, marble, and stone floors. No information available. Armstrong Flooring, Inc 2500 Columbia Ave. Lancaster, PA USA 17603	
Information Telephone No. : Website Address : 24 Hr Emergency Telephone # :	(800) 233-3823 <u>http://www.floorexpert.com</u> CHEM-TEL: 1-800-255-3924 OR 1-813-248-0585 (call collect)	
SECTION 2 – HAZARDS IDENTIFICATION		
GHS Classification per 29 CFR 1910.1200 (OSHA HCS 2012) and HPR (WHMIS 2015) Not classified as hazardous.		
GHS Pictograms		
Signal Word	None.	
Hazard Statements	None.	
	None.	
Safe Handling Instructions:	Avoid eye and skin contact. It is recommended to use safety glasses and gloves during handling. During installation process, adequate ventilation of the work area should be maintained. Although the product is low in VOCs, persons who are sensitive to odors or chemicals should avoid the work area during installation. Keep container closed.	
Hazards Not Otherwise Classified	None.	
% With Unknown Acute Toxicity :		

#### SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS #	% (by weight)
2-Butoxyethanol	111-76-2	0.1 – 1.0

## SECTION 4 – FIRST AID MEASURES

General Inhalation	<ul> <li>Call a doctor if you feel unwell.</li> <li>If inhaled, remove person to fresh air and keep at rest in a position comfortable for breathing. If breathing problems persist, seek medical attention/advice.</li> </ul>
Skin contact	: Remove contaminated clothing immediately. Wash skin with plenty of water. If irritations or symptoms develop, seek medical attention/advice.
Eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for 15 minutes. Get medical advice/attention.
Ingestion	: Rinse mouth. Do NOT induce vomiting. Call a doctor/physician if you feel unwell.

# **Armstrong**Flooring®

Lifeproof™ Resilient and Ceramic Floor Cleaner - Refill 12-March-2021 Armstrong Flooring, Inc. 2500 Columbia Ave. Lancaster, PA USA 17603 Telephone: (800) 233-3823 Page **2** of **6** 

12-101011-2021				
Notes for Physician	: Treat symptomatically.			
Signs and symptoms of short-te	rm (acute) exposure			
Inhalation	: None known.			
Skin	: Symptoms may include mild redness or itching.			
Eyes	: Symptoms may include mild redness, itching, or pain.			
Ingestion	: None known.			
Effects of long-term (chronic) ex	posure			
	: None known.			
Indication of need for immediate n	nedical attention or special treatment			
	: Difficulty breathing persists after removing the person to fresh air.			
	Any exposure to the eye which causes irritation.			
SE	CTION 5 – FIRE FIGHTING MEASURES			
Suitable extinguishing media	: Carbon dioxide, dry chemical powder, alcohol resistant foam or water spray.			
Unsuitable extinguishing media	: Water jet may spread the burning material.			
Hazardous combustion products	: Carbon dioxide; Carbon monoxide; Ammonia; Nitrogen oxides as well as other toxic vapors and gases which are common to thermal degradation of organic compounds.			
Special fire-fighting procedures/ed	quipment			
	: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. After fires have been extinguished, carefully clean all equipment and surfaces exposed to fumes.			
Environmental precautions	: Do not allow large amounts of this product to enter drains or contaminate ground water system.			
Fire hazards/conditions of flamma	bility			
	: Not flammable under normal conditions of use. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.			
Flammability classification (OSHA	-			
	: Not flammable.			
NFPA Rating	: 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe			
	Health: 1 Flammability 1 Instability 0 Special Hazards: None			
SECTIO	ON 6 – ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Restrict access to area until completion of clean-up. All persons dealing with clean-up should wear the appropriate chemically protective equipment.			
Protective equipment	<ul> <li>Refer to Section 8 for additional information on acceptable personal protective equipment.</li> </ul>			
Emorgonov Procedures	. This product doos not contain chamicals requiring EPA patification for spills			

**Emergency Procedures** : This product does not contain chemicals requiring EPA notification for spills.

#### Methods and materials for containment and cleaning up

Ventilate area of release. Stop spill or leak at source if safely possible. Caution: floor surfaces will be slippery! Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later disposal (see Section 13). Residual of product, while still wet, can be cleaned up with water. Notify the appropriate authorities as required.
 Prohibited materials
 None known.
 Do not allow large amounts of this product to enter drains or waterways, or contaminate ground water systems. Small amounts, such as used to clean floors, etc. may be disposed of by pouring down a drain.

# **Armstrong**Flooring®

Lifeproof™ Resilient and Ceramic Floor Cleaner - Refill 12-March-2021 Armstrong Flooring, Inc. 2500 Columbia Ave. Lancaster, PA USA 17603 Telephone: (800) 233-3823 Page **3** of **6** 

#### Reference to other sections

: See Section 14 for disposal information.

## SECTION 7 – HANDLING AND STORAGE

Safe handling procedures	d hygiene standard	ve equipment during handling. (See Section 8.) Observe ds. Use only with adequate ventilation. Wash thoroughly after ct with eyes, skin, or clothing.
Storage requirements		ell-ventilated area. Store away from heat and open flame. Iner. Keep tightly closed when not in use.
Incompatible materials	Section 10.	
Special packaging materials	special requiremen	its.

### SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Permissible Exposure Limits		ure limits have been he components in th		r the product	itself. Below are	exposure	
Ingredients		CAS #	ACGI	H TLV	OSHA PEL		
			TWA	STEL	PEL	STEL	
2-Butoxyethanol		111-76-2	20 ppm	N/Av	50 ppm (skin)	N/Av	
Engineering Controls	recomme	eral or local exhaus nded exposure lim f any vapor genera	its. Ventilatio	n should effe	ctively remove a		
Personal Protection Equipment							
Note		ring PPE recommen e product label.	dations are for	professional	users. Consume	er users should	
Eye / face protection	: Eye prote	ction such as chen	nical goggles	or safety glas	sses is recomme	ended.	
Skin protection	0	Wear gloves which are impervious to the product. Glove materials such as rubber or vinyl are recommended.					
Body protection		Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact.					
Respiratory protection	using this quantities	Under normal working conditions, respiratory protection is not necessary when using this product as recommended. If work process generates excessive quantities of vapor, or exposures in excess of any PEL, wear an appropriate organic vapor respirator.					
Site safety equipment	: An eyewa working a	ash station and safe area.	ety shower sh	ould be made	e available in the	e immediate	
General hygiene considerations		ntact with eyes, skii y. Remove soiled o					

#### **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

Physical state	:	Liquid	Appearance	:	Greenish-yellow
Odor	:	Ammonia	Odor threshold	:	N/Av
рН	:	9.5 - 10.5	Specific gravity	:	1.00
Boiling point	:	212°F (100°C)	Coefficient of water/oil distribution	:	N/Av
Melting/Freezing point	:	N/Av	Solubility in water	:	Miscible
Vapor pressure (mm Hg @ 20°C / 68°F)	:	N/Av	Evaporation rate ( <i>n</i> -Butyl acetate = 1)	:	N/Av
Vapor density (Air = 1)	:	N/Av	Volatiles (% by weight)	:	> 95 %
Volatile organic compounds (VOCs)	:	0.47% per CARB	rules		
Particle size	:	N/Av	Flammability classification	:	Not flammable

Lifeproof™ Resilient and Ceramic Floor Cleaner - Refill 12-March-2021

Flash point	:	>93.3°C (>200°F	) Lower flammable limit (% by vol)	:	Not available
Flash point method	:	Setaflash closed	Upper flammable limit (% by vol)	:	Not available
Auto-ignition temperature	:	N/Av	Decomposition temperature	:	Not available
Viscosity	:	N/Av	Oxidizing properties	:	Not available
Explosion data: Sensitivity to mechanical impact / static discharge					

: Not expected to be sensitive to mechanical impact or static discharge.

Armstrong Flooring, Inc. 2500 Columbia Ave. Lancaster, PA USA 17603 Telephone: (800) 233-3823

Page 4 of 6

### SECTION 10 – REACTIVITY AND STABILITY INFORMATION

Reactivity	Not reactive.
Stability	: Stable under the recommended storage and handling conditions prescribed.
Hazardous reactions	: Hazardous polymerization does not occur.
Conditions to avoid	Extreme heat.
Materials to avoid and incompatibility	
	: Strong oxidizing agents.
Hazardous decomposition products	
	: None known, refer to hazardous combustion products in Section 5.

SECTION 11 – TOXICOLOGICAL INFORMATION

010				
Routes of exposure	: Inhalation: YES	Skin Absorption: NO	Skin and Eyes:	YES Ingestion: YES
Symptoms of exposure	: See Section 4.			
Calculated Acute Toxicity Estimation	ates for the Product			
Inhalation	: > 300 mg/L			
Oral	: > 40,000 mg/kg			
Dermal	: > 40,000 mg/kg			
Toxicological data	: See below for indiv	idual ingredient acute to	kicity data.	
	LC50 (4 hr)		LD50	
Ingredients	Inhalation, rat	Oral, rat		Dermal, rabbit
2-Butoxyethanol	2.17	917		220
Serious eye damage / eye irritati Respiratory or skin sensitization Germ cell mutagenicity Carcinogenic status	<ul><li>None known.</li><li>None known.</li><li>Does not contain an concentrations greater</li></ul>	porary irritation to eyes. ny chemical listed as a ca ater than 0.1%. ACGIH c	lassifies 2-butox	yethanol in group A3-
Penroductive toxicity	a confirmed animai	carcinogen with unknow	in relevance to h	umans.
Reproductive toxicity				
Specific Target Organ Toxicity, S	: None known.			
Specific Target Organ Toxicity, F				
	: None known.			
Aspiration hazard	: None known.			
Additional information	: N/Av			

## **SECTION 12 – ECOLOGICAL INFORMATION**

**Environmental effects** 

: Under normal conditions of use, this product may be disposed of by pouring down a drain.

Lifeproof™ Resilient and Ceramic Floor Cleaner - Refill 12-March-2021

Ecotoxicity	:	No data available.
Biodegradability	:	No data available.
Bioaccumulative potential	:	No data available.
Mobility in soil	:	No data available.
PBT and vPvB assessment	:	No data available.
Other adverse effects	:	No data available.

## SECTION 13 – DISPOSAL CONSIDERATION

0	Handle waste according to recommendations in Section 7. Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.
Packaging	Handle contaminated packaging in the same manner as the product.
RCRA	For disposal of unused or waste material, check with local, state and federal environmental agencies.

### **SECTION 14 – TRANSPORTATION INFORMATION**

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	None	This product is not regulated according to Canadian TDG regulations.	None	None	None
TDG Additional Information	None			-1	I
49 CFR/DOT	None	This product is not regulated according to US DOT regulations.	None	None	None
		DOT regulations.			

IATA IMDG : Not regulated for Air Transport

: Not regulated for Ocean Transport

### **SECTION 15 – REGULATORY INFORMATION**

#### Canadian Information:

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR). This SDS contains all of the information required by the HPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on either the Domestic Substances List (DSL) or the Non- Domestic Substances List (NDSL).

#### **US Federal Information:**

TSCA: All ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Not Hazardous.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above *de minimus* concentrations.

#### U.S. State Right To Know Laws

California Proposition 65: None

Armstrong Flooring, Inc. 2500 Columbia Ave. Lancaster, PA USA 17603 Telephone: (800) 233-3823 Page **5** of **6** 

Lifeproof™ Resilient and Ceramic Floor Cleaner - Refill 12-March-2021

Other State Right to Know Laws:

Ingredient on State RTK Law?	CAS No.	CA	MA	MN	NJ	NY	PA	RI
2-Butoxyethanol	111-76-2	Yes	Yes	Yes	Yes	No	Yes	Yes

#### **SECTION 16 – OTHER INFORMATION**

HMIS Rating

: \*- Chronic Hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe Health: 1 Flammability 1 Physical Hazard: 0 PPE: Gloves, safety glasses

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists CAS: Chemical Abstract Services CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980 CFR: Code of Federal Regulations DOT: Department of Transportation DSL: Domestic Substances List EPA: Environmental Protection Agency GHS: Globally Harmonized System HPR: Hazardous Products Regulations IARC: International Agency for Research on Cancer Inh: Inhalation N/Av: Not Available N/Ap: Not Applicable NIOSH: National Institute of Occupational Safety and Health NTP: National Toxicology Program OSHA: Occupational Safety and Health Administration PEL: Permissible exposure limit RCRA: Resource Conservation and Recovery Act SARA: Superfund Amendments and Reauthorization Act STEL: Short Term Exposure Limit TDG: Canadian Transportation of Dangerous Goods Act & Regulations TLV: Threshold Limit Values TSCA: Toxic Substance Control Act TWA: Time Weighted Average WHMIS: Workplace Hazardous Materials Identification System

#### **Disclaimer of Liability**

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

No warranty of any kind is given or implied. Armstrong Flooring, Inc. will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein.

#### Prepared By:

Armstrong Flooring, Inc. 2500 Columbia Ave. Lancaster, PA, USA 17603

(800) 233-3823 Visit our Website: http://www.floorexpert.com

Revision date:	: 12-March-2021
----------------	-----------------

:	01-Jul-2019
	:

End of Document