ArmstrongFlooring® QUIET COMFORT SOUND CONTROL™

LUXURY SOUND CONTROL FLOORING UNDERLAYMENT

Quiet Comfort Sound Control™ is a high-performance, cross-linked polypropylene foam underlayment engineered to enhance sound reduction and moisture resistance beneath luxury flooring installations. Designed to deliver a quieter, more comfortable floor while supporting long-term performance.

KEY BENEFITS

- **Sound Reduction:** Helps reduce both impact and ambient noise for quieter spaces.
- **Enhanced Comfort:** Adds cushioning underfoot and compensates for minor subfloor imperfections.
- **Moisture Resistance:** Built in moisture resistant construction.
- **Versatile:** Float over subfloor or install using adhesive.

RECOMMENDED FLOORING APPLICATIONS

- Luxury Vinyl Tile-LVT (3.2 mm or greater)
- Not for use in areas with heavy rolling loads or static loads greater than 250 psi

SPECIFICATIONS

- Package contains 300 square feet of underlayment
- .040" (1 mm) overall average thickness
- 6 ft. wide x 50 ft. long

INSTALLATION INSTRUCTIONS

- Make sure subfloor is clean, flat, dry, and free of all debris.
- Begin in corner and install Quiet Comfort Sound Control parallel to the wall in the opposite direction you will install the floor planks.
- Leave at least 2" of excess Quiet Comfort Sound Control up the wall and trim after installation is complete.
- Roll out the next piece of Quiet Comfort Sound Control, making sure the seams are butted together.
- Use a good quality packing tape, at least 2" wide to attach seams.

Visit FloorExpert.com
For SDS or complete product, technical, installation, maintenance, and warranty details.

floor score
CERTIFIED BY SCS Global Services

MADE IN THE USA

FloorScore® is a trademark of the Resilient Floor Covering Institute. All other trademarks owned by AHF, LLC. © 2026 AHF, LLC.
Manufactured in the USA for AHF, LLC., 3840 Hempland Road, Mountville, PA USA 17554
+1-866-243-2726 ArmstrongFlooring.com
01840101 626

4 23698 82507 4