

LATERAL™

Roller-Applied Adhesive for Wall & Floor Installations

Lateral™ is the go-to adhesive for interior wall applications of luxury vinyl in commercial environments. Pressure sensitive and FloorScore® certified, Lateral is fast-drying for a quick and easy installation process. Lateral may also be used for flooring installations in light commercial and residential environments.

SKU: ADH600




* Visual may not be representative of actual packaging

Features:

- Go-to wall adhesive
- Two coat-roller applied recommended
- Instant grab
- Dries quickly
- High-performing bond
- Shelf life: 2 years

Recommended Tools:



3/8" (10 mm)
short nap paint roller

Important

Keep paint roller wet! Do not apply pressure to the roller, allow it to freely roll over the substrate.

Adhesive coverage must not exceed **400 ft²/gal.** All surfaces require two coats of Parterre Lateral™ Roller-Applied adhesive including latex primed, porous or slightly textured surfaces.

Weights/Spread Rate			Maximum Moisture and pH Levels	
Size	Weight	Porous and Non-Porous Substrates	RH Max	pH Range
1 gal.	9 lb.	350-400 sq. ft./gal.	90%	8-10
4 gal.	36 lb.	1,400-1,600 sq. ft./gal.		

For installation technical manual, visit: parterreflooring.com/technical

For more information contact us at parterreflooring.com or 888.338.1029.

